

Direct to Process / PB

	N2 / O2 / Ar	CO2 PB	CO2 Process	
Model No (240 / 480 volts)	Kilowatts	SCFH	lbs./hr	lbs./hr
240/480C-15-.5-XX-LTCO/PBU	15	3,500 / 1,300	200	170
240/480C-30-.5-XX-LTCO/PBU	30	3,500 / 3450	200	375
240/480C-45-.5-XX-LTCO/PBU	45	3,500 / 6900	200	750
240/480C-60-.5-XX-LTCO/PBU	60	3,500 / 10,350	200	1,125
240/480C-75-.5-XX-LTCO/PBU	75	3,500 / 13800	200	1,500
240/480C-90-.5-XX-LTCO/PBU	90	3,500 / 17250	200	1,875
240/480C-105-.5-XX-LTCO/PBU	105	3,500 / 20700	200	2,250
240/480C-120-.5-XX-LTCO/PBU	120	3,500 / 24150	200	2,625
240/480C-135-.5-XX-LTCO/PBU	135	3,500 / 27600	200	3,000
240/480C-150-.5-XX-LTCO/PBU	150	7,000 / 31,050	400	3,375
240/480C-165-.5-XX-LTCO/PBU	165	7,000 / 34,500	400	3,750